

DEUTZ TCD 5.2 L4


Powerful, efficient and compact.



For mobile machinery

The TCD 5.2 – With 100 up to 170 kW power output ideal for your application.



- **POWERFUL** / Up to 170 kW & 950 Nm
- **LOW EMISSIONS** / EU St. V & US Tier 4 certified; HVO ready
- **MODULAR** / Wide range of applications due to a variety of options
- **VERSATILE** / EDG - version*



*Emission Downgrade without EAT

DEUTZ TCD 5.2


TCD 5.2



TECHNICAL DATA

ENGINE TYPE		TCD 5.2
No. of Cylinders		4
Displacement	l	5.2
Max. Nominal Speed	min ⁻¹	2300
Aspiration		Turbocharger with charge air cooler
Power Output acc. ISO 14396	kW	170
At Speed	min ⁻¹	1800
Max. Torque	Nm	950
At Speed	min ⁻¹	1300
Min. Idling Speed	min ⁻¹	800
Weight (DIN 70020 Part 7A)	kg	approx. 530

DIMENSIONS



		DOC/DPF				SCR			DOC/DPF	SCR
ENGINE TYPE		A	B	C	D	L	D	L		
TCD 5.2	mm	949	753	973	318	640	289	635	● ●	● ●

● Standard for US Tier 4
● Standard for EU Stage V



DEUTZ AG
Ottostraße 1
51149 Cologne
Germany
www.deutz.com